



Wirepas 5.1 tags and Wirepas Anchors

Item Part Number	Wirepas5.1-IT001	Wirepas5.1-IT002	Wirepas5.1-KF001	Wirepas5.1-IT004	Wirepas5.1-IT005	Wirepas5.1-IT008	Wirepas5.1-WB400	Wirepas5.1-WB100	Wirepas5.1 Anchor-IT005 & IT005+	Wirepas5.1 Anchor-IT005-AC	Wirepas5.1-Anchor-IT008 & IT008+	BOP01	
Protocols	Wirepas5.1 stack supported								Wirepas anchor stack supported	Wirepas 5.1 stack, Quuppa, iBeacon, Eddystone	Wirepas anchor stack supported	Beacon opener only for IT001, IT002, and KF001	
Dimensions (mm)	48 x 11	64.4 x 11	50 x 35 x 11.5	32.6 x 8.7	70 x 49 x 22	91.5 x 49 x 22	Tag: 41x31 Band: 250 x 15	Tag: 36.5 x 32 x 11 Band: 241	70 x 49 x 22 (36.8 4AA)	70 x 49 x 22	91.5 x 49 x 22 (36.8 4AA)	36 x 24	
Standard Color	black ring white inside	black ring white inside	black ring white inside	White	White top, black bottom		White tag black nylon band	white	White top, black bottom				
Material	PC/ABS						ABS tag nylon band stainless steel	Silicone Stainless steel	PC/ABS			Aluminium alloy	
Battery type	CR2032		Replaceable		2xAA Replaceable		CR2032		2.6 Ah (2xAA) or 5.2Ah (4xAA) Replaceable	Power supply 110/240 V	2.6 Ah (2xAA) or 5.2Ah (4xAA) Replaceable	N/A	
Battery lifetime	up to 3 years		up to 5 years		up to 8 years		up to 3 years		up to 8 years	N/A	up to 8 years	N/A	
Transmission Range	up to 100 meters								LOS (Line Of Sight) of 200 meters			N/A	
Operating & Storage temperature	-30°C up to +60°C				-20°C up to +54°C, others on request		-30°C up to +60°C		-20°C up to +54°C, others on request	0°C up to +40°C	-20°C up to +54°C, others on request	N/A	
Printing	Silk screen printing Laser						Offset printing Silk screen printing		Silk screen printing Laser			N/A	
Press Switch Button	Yes								Yes			N/A	
Sensor	Accelerometer sensor								Accelerometer sensor			N/A	
LED's	Optional		2		1		2		Optional			N/A	
Other options	NFC Forum Tag			Temperature sensor NFC Forum Tag		NFC Forum Tag						N/A	
Beacon attachment	Strong adhesive, others	Screws Rivets	Key ring	Strong adhesive	Strong adhesive Velcro, others	Screws Rivets	Wrist			Strong adhesive Velcro, others	Optional foam adhesive	Screws Rivets	N/A
Power Connection	N/A								N/A	Loose cable ~14cm for AC connectors	N/A	N/A	
IP rating	IP68		IP65		IP68		IP65		IP68			N/A	
Certifications	CE, FCC, IC, RoHS, Reach												

Rev.01 - 220403

Tatwah Technology Co., Ltd. reserves the rights to change any information or data in this document without prior notice.

Tatwah Technology Co., Ltd. - www.mango-rfid.com
No.9 Shuiyi South Road, Taifeng Industrial Park, Xiaolan Town, Zhongshan City, Guangdong Province, China, 528415

tatwah SA (Back Office) - www.tatwah.net
Rue de Lausanne 47, CH-1110 Morges, Switzerland

